



Mounting Suggestions for the Harley-Davidson® Softail Deuce 2000-2007 Two-Piece Seat

- Hardware:
- Stock Rear Fender Screw

Baseplate Features:

All seats are built on fiberglass baseplates. The baseplates have rubber supports at contact points. A built-in support wing holds up the full width of the foam.



Removal of Stock One-Piece Seat

1. Remove rear fender screw.
2. Slide seat back and up to remove.



Mounting of Mustang Seat

Solo Seat

1. Remove front Allen bolt used to secure fender strut.
2. Remove spacer washer between strut and frame.
3. Clip welded nose tab into the frame mount behind the fuel tank just like the stock seat.
4. Align side brackets behind fender strut.
5. Install Allen bolts.



Passenger Seat

6. Remove stock seat bracket and install it onto the back of the Mustang passenger seat.
7. Slide front passenger seat bracket into receiver located at back of Mustang's solo seat as far as it can go.
8. Align rear bracket with fender nut and secure.



Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>