



Mounting Suggestions for the Harley-Davidson® Dyna Glide & Dyna Wide Glide 1991- 1995 One-Piece Seat

Tools Required:

- Phillips Screwdriver

Hardware:

- Stock Rear Fender Screw
- Short Chrome Bracket for Dyna Glide (Included)
- Long Chrome Bracket for Dyna Wide Glide (Included)



Dyna Glide Bracket Shown

Baseplate Features:

One-piece formed steel baseplates have rubber bumper supports at contact points. Two brackets are supplied that bolt to the rear of the Mustang seat. Use the long bracket for Dyna Wide Glide models and the short bracket for standard Dyna Glide models.

Removal of Stock Seat

1. Remove rear fender screw and set aside. The stock rear fender screw will be used to attach your new Mustang One-Piece Seat.
2. If applicable, remove seat strap.
3. Slide seat back and lift up.

Mounting of Mustang Seat

1. Secure rear bracket to baseplate of passenger seat with supplied screws. Use long bracket for Dyna Wide Glide models and short bracket for Dyna Glide models. (Fig. 1)
2. Engage nose bracket under welded frame tab.
3. Align chrome rear tab located at back of passenger seat with hole in fender.
4. Secure with stock fender screw to complete the installation process.

Fig. 1



Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>