



Mounting Suggestions for the Harley-Davidson® FLHT and FLTR Road Glide 1997-2007 Two-Piece Seat

Hardware:

- Stock Rear Fender Screw
- 1997-1998: Two Black Flat Nylon Washers (Included); Mustang Part #78028 (Not Included) or Stock H-D
- 1999-2007: Two Black Nylon Shoulder Washers (Included); Mustang Part #78032 (Not Included) or Stock H-D
- One Nylon Washer (Included)

Baseplate Features:

Built on 16 gauge formed steel baseplates. Solos have a single nose clip and two chrome mounting tabs that align with the fender inserts. Passenger seats have two slots in the baseplate and a chrome tab for mounting.



Removal of Stock One-Piece Seat

1. Remove rear fender screw.
2. Slide seat back and up to remove.

Mounting of Mustang Solo

1. Engage nose of seat, pushing seat as far forward as possible so that the mounting holes/studs in the fender are in the middle to back edge of the slotted tabs.
2. A firm downward chop to the nose of the seat will push the seat closer to the dash.
3. Seat is spring loaded for a tight fit so the mounting tabs will be approximately 1"-1 1/2" above the fender.
4. The supplied nylon washers go between the mounting tabs and the fender.
5. Start one mounting bolt/nut to finger tight and then do second, secure both.
6. 1997-1998 models require that the black retention clip must be left in place to hold the nut insert in 1997-1998 models require seat mounting bolts (Mustang part #78028) or stock Harley-Davidson®.
7. 1999-2007 models: the studs in the fender have some movement to help with lining up the tabs. 1999-2007 models: require Road King seat mounting nuts (Mustang part #78032 or stock H-D). (Fig. 1)

Fig. 1



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>

Mounting of Mustang Passenger Seat

1. Front of baseplate is slotted and engages into the bolts/nuts in the fender at the rear of the solo seat.
2. The supplied nylon washer goes between the rear mounting tab and the fender, secure with rear fender screw.
3. The black retention clip that holds the nut insert in the fender must remain in place.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>