



## Mounting Suggestions for the 2008-09 Harley-Davidson® Road King, Road King Classic, FLHX, FLTR, FLHT Rear Seat

### Tools Required:

- Phillips Screwdriver

### Hardware:

- Stock Rear Fender Screw
- Black Nylon Washer (Included)



### **Baseplate Features:**

Rear seats are built on 16 gauge formed steel baseplates and have two slots in the front of the baseplate and a single chrome rear mounting tab.

### **Removal of Stock Passenger Seat**

1. Remove the rear fender screw. This screw will be used later to secure your new Mustang Rear Seat.
2. Slide the passenger seat back and up.

### **Mounting of Mustang Rear Seat**

1. Front of baseplate is slotted and engages into the slotted nuts (Mustang Part #78032 or H-D Equivalent) at the rear of the solo seat.
2. The supplied black nylon washer goes between the rear mounting tab and the fender.
3. Secure with stock rear fender screw. The black retention clip that holds the nut insert in the fender must remain in place.

**Enjoy the Comfort of your new Mustang Seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at <http://www.mustangseats.com>