



Mounting Suggestions for the 2008-09 Harley-Davidson® Road King, Road King Classic, FLHX, FLTR, and FLHT Solo Seat

Tools Required:

- Phillips Screwdriver
- 5/8" Deep Socket or Open-End Wrench
- 7/16" Open-End Wrench

Hardware:

- Solo Seat Mounting Nuts Mustang Part#78032 or H-D equivalent (Not Included)
- Black Nylon Shoulder Washer x 2 (Included)
- 1/4" Chrome Washer x 2 (Included)



Baseplate Features:

The solo features a 16 gauge formed steel baseplate and is a direct replacement for the stock solo. The solo has a single nose clip and two chrome mounting tabs that align with the fender studs.

Stock Passenger Seat Removal Steps

1. Remove the rear fender screw.
2. Slide the passenger seat back and up.

Stock Solo Seat Removal Steps

1. Remove the solo mounting nuts located at the back of the solo seat.
2. Slide the solo back and up.

Stock One-Piece Seat Removal Steps

1. Remove the rear fender screw.
2. Remove hand strap that is secured to the motorcycle on each side of the seat where the front saddle bag mount is located.
3. Slide the stock seat back and up.

NOTE: To mount your new Mustang Solo seat you will need Seat Mounting Nuts, Mustang Part#78032 or H-D equivalent, which are not included and must be purchased separately.

Mustang Part#78032



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>

Mounting of Mustang Seat

1. Engage nose of seat, pushing seat as far forward as possible so that the mounting studs in the fender are in the middle to back edge of the slotted tabs.
2. A firm downward punch or chop to the nose of the seat will push the seat closer to the chrome dash.
3. The seat is spring loaded so the rear tab will be above the fender approximately 1" to 1 1/2".
4. The supplied nylon washers go between the mounting tabs and the fender.
5. Supplied Chrome Washers go between mounting tabs on seat and solo mounting nuts.
6. Start one mounting nut to finger tight and then do second, secure both.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>