



Mounting Suggestions for the Harley-Davidson® Road King 1994-1996 One-Piece Seat

Hardware:

- Stock Fender Screw
- Fender Bracket (Included)



Baseplate Features:

One-Piece Touring Seats are constructed on a marine-grade fiberglass baseplate. The baseplate is slotted in the middle to allow for the use of a Mustang or stock Harley-Davidson® driver backrest kit.

Removal of Stock Seat

1. Remove rear fender screw.
2. Slide passenger seat back and up.
3. Remove solo mounting bolts located at back of solo, 5/16"-24 thread on 1994 models or 5/16-18" thread on 1995-96 models.
4. Slide solo seat back and up.

Mounting of Mustang Solo

1. Unbolt fender bracket from underside of Mustang seat.
2. Secure bracket to fender using stock solo bolts.
3. Engage front nose clip into tab on frame.
4. Lower rear of seat down to fender aligning two studs on bottom of seat into fender bracket.
5. Secure chrome rear fender bracket to fender with stock screw.
6. Fasten fender bracket to seat with supplied washers and nuts.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>