



Mounting Suggestions: Harley-Davidson® Softail 2000-04 Two-Piece Seat

Baseplate Features:

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points and carpet to protect the fender. Mustang Softail solos have to removable side brackets.

NOTE: Mustang Softail seats will fit all Softail models except 1999 and earlier FLSTS Heritage Springers.



Removal of Stock Seat

1. Remove one side mounting bolt on each side of solo.
2. Remove rear fender screw.
3. Slide seat back and up.



Mounting of Mustang Seat

1. Remove two screws located at back of Mustang solo seat.
2. Align passenger seat front chrome tabs with holes in back of solo baseplate.
3. Secure passenger seat and solo together with screws from step 1.
4. Clip welded nose tab into the frame mount behind the fuel tank.
5. Align side brackets with large threaded holes in frame.
6. Secure side brackets with stock bolts or Mustang's chrome solo bolts part #78033 (sold separately)
7. Align chrome rear tab with threaded fender hole and secure with stock screw.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>