



Mounting Suggestions: Harley-Davidson® Softail 1984-06 & 2007 FLSTSC Springer, FLSTC Heritage and FLSTN Deluxe One-Piece Seat

Baseplate Features:

All seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points and carpet to protect the fender.




HD#52467-00
(sold through dealers)

2000-05 models require the stock rear mounting bracket (HD# 52467-00) be removed from the stock seat and bolted to the Mustang seat.

Softail Mounting Hardware

For Model:

Use

2000-05 FLSTS Heritage Springer 2005-07 FLSTN Deluxe 2006-07 FLSTSC Springer Classic 2006 FLST Heritage	Required Part #78116 Rear Seat Bracket with screw.	
2006 FLSTF Fat Boy 2006 FLSTC Heritage Classic	Required: Stock rear mounting bracket with captive screw.	

Removal of Stock Seat

1. Unscrew slotted solo side screws.
2. Unscrew rear fender screw. NOTE: Spring loaded screws stay attached to brackets.
3. Slide seat back and up.

These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>

**Mounting Suggestions: Harley-Davidson® Softail 1984-06
& 2007 FLSTSC Springer, FLSTC Heritage and FLSTN Deluxe One-Piece Seat**

Mounting of Mustang Seat

1. Remove stock rear mounting bracket (HD #52467-00 mounting bracket sold through dealers) from stock seat and bolt to the Mustang seat.
2. Insert welded nose tab into the frame mount behind the fuel tank.
3. Secure rear stock screw into threaded fender hole.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>