



## Mounting Suggestions: Harley-Davidson® Softail 1984-99 Passenger Seat

### **Baseplate Features:**

Seats are built on 16 gauge formed steel baseplates. The baseplates have rubber supports at contact points and carpet to protect the fender. All passenger seats are connected to the solo with two hidden screws.

NOTE: Mustang softail seats will fit all Softail models except 1999 and earlier FLSTS Heritage Springers.

### **Removal of Stock Passenger Seat**

1. Remove one side mounting bolt on each side of solo.
2. Remove rear fender screw.
3. Slide seat back and up.

### **Mounting of Mustang Passenger Seat**

1. Remove two screws located at back of Mustang solo seat.
2. Align passenger seat front chrome tabs with threaded holes in back of solo baseplate.
3. Secure rear seat and solo together with screws from step 1.
4. Align chrome rear tab with threaded fender hole and secure with stock screw.

NOTE: Mustang passenger seat can only be mounted to a Mustang solo seat.

**Enjoy the Comfort of your new Mustang Seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at <http://www.mustangseats.com>