



## Mounting Suggestions: Honda Valkyrie 1997-03 Two-Piece Seat



### Baseplate Features:

The two-piece, marine-grade fiberglass baseplate is a direct replacement for the stock one-piece seat. Rubber bumpers are strategically placed to prevent the seat from touching the frame and fender.

### Stock Seat Removal Steps

1. Unlock solo with the ignition key.
2. Pull nose of solo up and slide forward to remove.
3. Remove two 5 mm Allen bolts in the front of passenger seat and one 8 mm Allen bolt at the rear of passenger seat.
4. Remove passenger seat.

Note: When passenger seat is removed, fender will have no brackets.

### Mounting of Mustang Seat

1. Passenger seat is mounted first. Secure with one stock 8 mm bolt in rear and two stock 5 mm bolts in front.
2. Solo is mounted by engaging rear tab into fender mount and locking front latch.

Note: If solo seat does not line up with the front latch, the rear tab is not properly engaged. The skirt on the solo seat must not be bent under seat.

**Enjoy the Comfort of your new Mustang Seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at <http://www.mustangseats.com>