



Mounting Suggestions: Honda Valkyrie Interstate 1999-01 Two-Piece Seat

Hardware

- Two 6 mm Allen Bolts, Mustang Part #78042 (Required, are included at no charge with an Interstate seat order upon your specific request)



Baseplate Features:

The two-piece, marine-grade fiberglass baseplate is a direct replacement for the stock one-piece seat. Rubber bumpers are strategically placed to prevent the seat from touching the frame and fender.

Stock Seat Removal Steps

1. Unlock and pull the nose of the seat up.
2. Slide entire seat forward.

Mounting of Mustang Seat

Note: The two weld nuts under fender are covered with 0.5" round stickers. Remove the stickers before fastening the rear seat.

1. Attach the rear of the passenger seat to fender just above the taillight, using the stock 6 mm Allen bolt. It may be necessary to lift up the rear of the fender to properly engage the 6 mm bolt. The front of the seat is secured to the fender using the two (supplied) 6 mm Allen bolts.
2. Slide rear of solo into receiver on fender, push nose down into key latch mechanism.

Enjoy the Comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at <http://www.mustangseats.com>