



MOUNTING SUGGESTIONS:

Kawasaki Vulcan 800 Tank Bib

Installation of Mustang tank bib:

1. Remove the seat, then remove the three dash mounting bolts.
2. Lift the dash and position the small square hole around the lower dash mount.
Note: The tank collar must remain with the dash. The bib goes under both the collar and the chrome dash.
3. Re-install the dash with the stock mounting bolts.
4. Remove the tank bolt and collar insert from the rear of the tank.
5. Push the collar insert through the bib's lower mounting hole, align with the tank mount, and secure with the stock mounting bolt.
6. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93117, 93118

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.